



2-V Cell Series

Product Code	Voltage, V	10-hr Capacity, Ah (discharged to 1.80 V)	Length, mm	Width, mm	Height, mm	Total Height, mm	Terminal Type	Layout	Approx. Weight, kg
OM-02-0065	2	65	170	72	205	214	M6	B	4.5
OM-02-0100	2	100	170	72	205	214	M6	B	5.8
OM-02-0120	2	120	170	98	205	214	M6-18	G	7.2
OM-02-0150	2	150	170	98	205	214	M6-18	G	8.4
OM-02-0200	2	200	170	110	328	348	M8	G	13.5
OM-02-0250	2	250	170	110	328	350	M8	G	14.3
OM-02-0300	2	300	170	150	328	348	M8	G	18.8
OM-02-0350	2	350	170	150	328	348	M8	G	19.2
OM-02-0400	2	400	210	175	330	350	M8	G	25.5
OM-02-0450	2	450	210	175	330	350	M8	G	26.0
OM-02-0500	2	500	240	175	330	350	M8	G	30.0
OM-02-0600	2	600	300	175	330	350	M8	H	37.0
OM-02-0800	2	800	410	175	330	350	M8	H	50.4
OM-02-1000	2	1000	475	175	328	350	M8	I	60.0
OM-02-1200	2	1200	475	175	328	350	M8	J	63.8
OM-02-1500	2	1500	403	354	339	349	M8	K	97.8
OM-02-2000	2	2000	490	350	339	349	M8	F	121.0
OM-02-3000	2	3000	709	350	337	347	M8	L	183.0

4-V Cell Series

Product Code	Voltage, V	20-hr Capacity, Ah (discharged to 3.50 V)	Length, mm	Width, mm	Height, mm	Total Height, mm	Terminal Type	Layout	Approx. Weight, kg
OM-04-004.5	4	4.5	53	48	94	100	T1	C	0.6
OM-04-010	4	10	102	50	93	99	T2	C	1.1

6-V Cell Series

Product Code	Voltage, V	20-hr Capacity, Ah (discharged to 5.25 V)	Length, mm	Width, mm	Height, mm	Height, mm	Terminal Type	Layout	Approx. Weight, kg
OM-06-001	6	1.0	51	42	51	57	T1	B	0.3
OM-06-001.2	6	1.2	97	24	52	58	T1	C	0.3
OM-06-002	6	2.0	43	37	76	76	Special Design	M	0.3
OM-06-002.8	6	2.8	66	33	97	103	T1	B	0.6
OM-06-003.2	6	3.2	134	34	60	66	T1	C	0.6
OM-06-004	6	4.0	70	47	100	106	T2	B	0.7
OM-06-004.5	6	4.5	70	47	100	106	T1	B	0.8
OM-06-004.5	6	4.5	70	47	100	106	T2	B	0.7
OM-06-004.5	6	4.5	67	67	96	109	Spring	O	0.8
OM-06-005	6	5.0	170	35	70	74	T1	C	1.0
OM-06-005.4	6	5.4	70	47	100	106	T1	B	0.8
OM-06-006	6	6.0	70	47	100	106	T1	B	0.9
OM-06-007	6	7.0	150	34	94	100	T1	C	1.0
OM-06-007.2	6	7.2	150	34	94	100	T2	C	1.1
OM-06-007.5	6	7.5	150	34	94	100	T1	C	1.3
OM-06-008	6	8.0	150	34	94	100	T1	C	1.3
OM-06-008.5	6	8.5	150	34	94	100	T2	C	1.2
OM-06-008.5	6	8.5	98	56	118	120	T1	A	1.4
OM-06-010	6	10	151	51	94	100	T1	C	1.5
OM-06-012	6	12	151	51	94	100	T2	C	1.6
OM-06-013	6	13	108	70	140	140	T1-/T2+	F	2.2
OM-06-014	6	14	151	51	94	100	T2	C	1.9
OM-06-020	6	20	157	83	125	125	T4	C	3.2
OM-06-036	6	36	161	87	163	169	T2	A	5.1
OM-06-060	6	60	185	112	205	205	T2	F	9.1
OM-06-200	6	200	322	178	226	232	M8	B	30.3

8-V Cell Series

Product Code	Voltage, V	20-hr Capacity, Ah (discharged to 7.00 V)	Length, mm	Width, mm	Height, mm	Total Height, mm	Terminal Type	Layout	Approx. Weight, kg
OM-08-003.2	8	3.2	134	37	63	69	T1	F	0.8

TERMINAL TYPE
 A-PENCIL POST
 B-STANDARD
 C-SPECIAL MARINE
 D-U1
 E-STUD
 F-DUAL MARINE
 G-SIDE TERMINAL
 H-DUAL TERMINAL

FINISH COVER-CONTAINER
 M-M / MATTE-MATTE
 G-M / GLOSSY-MATTE
 G-G / GLOSSY-GLOSSY

12-V Cell Series

Product Code	Voltage, V	20-hr Capacity, Ah (discharged to 10.50 V)	Length, mm	Width, mm	Height, mm	Total Height, mm	Terminal Type	Layout	Approx. Weight, kg
OM-12-000.8	12	0.8	96	25	62	62	Connector	N	0.3
OM-12-001.2	12	1.2	97	43	52	58	T1	F	0.5
OM-12-001.9	12	1.9	178	35	60	66	T1	C	0.9
OM-12-002.2	12	2.2	71	48	97	103	T1	C	0.8
OM-12-002.3	12	2.3	178	35	60	66	T1	C	0.9
OM-12-002.8	12	2.8	133	34	98	104	T1	C	1.1
OM-12-002.9	12	2.9	79	56	99	105	T1	D	1.1
OM-12-003.5	12	3.5	134	67	60	66	T1	F	1.2
OM-12-004	12	4.0	151	65	94	100	T2	C	1.4
OM-12-004	12	4.0	90	70	101	107	T2	C	1.3
OM-12-004.5	12	4.5	90	70	101	107	T2	C	1.4
OM-12-005	12	5.0	151	53	93	99	T1	E	1.7
OM-12-005.4	12	5.4	90	70	101	107	T1	C	1.8
OM-12-006	12	6.0	90	70	101	107	T2	C	1.9
OM-12-006.5	12	6.5	151	51	93	99	T2	E	1.8
OM-12-006	12	6.0	151	65	94	100	T2	E	1.8
OM-12-007	12	7.0	151	65	94	100	T1	E	2.0
OM-12-007.5	12	7.5	151	65	94	100	T2	E	2.3
OM-12-008	12	8.0	151	65	94	100	T2	E	2.5
OM-12-008.5	12	8.5	151	65	94	100	T2	E	2.4
OM-12-009	12	9.0	151	65	94	100	T2	E	2.5
OM-12-010	12	10	151	98	95	101	T2	E	3.1
OM-12-010	12	10	151	65	111	117	T2	E	3.1
OM-12-012	12	12	151	98	95	101	T2	E	3.2
OM-12-014	12	14	151	98	95	101	T2	E	3.8
OM-12-015	12	15	182	77	168	168	T3	D	4.7
OM-12-018	12	18	182	77	168	168	T3	D	5.4
OM-12-020	12	20	182	77	168	168	M5	D	5.7
OM-12-024	12	24	166	175	125	125	T3	D	7.2
OM-12-024	12	24	164	125	174	174	M5	D	8.5
OM-12-026	12	26	166	175	125	125	M5	D	7.8
OM-12-028	12	28	166	175	125	125	T3	D	8.4
OM-12-028	12	28	164	125	174	174	M5	D	9.1
OM-12-030	12	30	195	130	164	167	M6	C	9.3
OM-12-030	12	30	195	130	164	178	T5	C	9.3
OM-12-033	12	33	195	130	164	178	T5	C	10.2
OM-12-035	12	35	195	130	164	178	T5	C	10.7
OM-12-038	12	38	197	165	170	170	M6	D	12.0
OM-12-040	12	40	197	165	170	170	M6	D	13.7
OM-12-045	12	45	197	165	170	170	M6	D	14.2
OM-12-050	12	50	257	132	200	200	M6	C	15.7
OM-12-055	12	55	229	138	205	211	M6	C	16.2
OM-12-060	12	60	260	168	208	214	M6	C	18.4
OM-12-075	12	75	260	168	208	214	M6	C	22.3
OM-12-080	12	80	260	168	208	214	M6	C	23.8
OM-12-090	12	90	330	173	212	220	M8	C	27.8
OM-12-100	12	100	330	173	212	220	M8	C	28.0
OM-12-140	12	140	345	172	274	280	M8	C	41.2
OM-12-070	12	70	348	167	178	178	M6	C	21.4
OM-12-065	12	65	348	167	178	178	M6	C	19.2
OM-12-120	12	120	408	177	225	225	M8	C	35.0
OM-12-150	12	150	483	170	239	239	M8	C	43.2
OM-12-180	12	180	532	207	214	220	M8	F	51.0
OM-12-200	12	200	522	240	218	224	M8	F	59.8
OM-12-250	12	250	522	268	220	226	M8	F	70.6